



Recommended Minimum Pool
Area Reserved For Each
Slide Operation Is 23'-8" x 20' With
Minimum Water Depth Of 36".

BASE SPECS

	"A"	"B"
Ride Length	204.39'	211.42'
Centerline Length	174.53'	184.95'
Tower Height	26'-10"	26'-10"
Landing Height	17'-6"	17'-6"
Landing Height	9'-11"	9'-11"
Slope	14.75%	14.89%
Flume Type	Open	Open
Flume Width	36.00"	36.00"
Centerline Radius	52.00"	72.00"
Stairway Width	36.00"	36.00"
Stairway Config	7/11	7/11
Designed Water Flow	800 GPM	800 GPM
Pump Motor	10 HP	10 HP

PRELIMINARY LAYOUT – FOR REVIEW AND APPROVAL ONLY.
SPECIFICATIONS SUBJECT TO CHANGE.
NOT FOR CONSTRUCTION



USA SLIDE, INC
1180 AIRPORT PARKWAY
GAINESVILLE, GEORGIA
30501 USA

PHONE: 770 297 1551
1 800 872 7543
FAX: 770 297 9633
www.usaslide.com

CONFIDENTIAL – PROPERTY OF USA SLIDE, INC

CUSTOM AQUAADRENALINE SLIDE

MODEL CAAF-215R3	DRAWN BY RLP	DWG. DATE OCT 12, 2010
DWG SCALE 3/32" = 1'-0"	REVISION 0	DWG. NO. CAA215R3