



Recommended Minimum Pool Area Reserved For Slide Operation Is 13'-0" x 20' With Minimum Water Depth Of 36"

Recommended Minimum Pool Area Reserved For Slide Operation Is 13'-0" x 20' With Minimum Water Depth Of 36"

**BASE SPECS**

	A	B
Ride Length	121.22'	126.43'
Centerline Length	100.72'	105.27'
Tower Height	14'-7"	14'-7"
Landing Height	8'-2"	8'-2"
Slope	14.88%	14.22%
Open Flume Width	36.00"	36.00"
Centerline Radius	52"/72"	52.00"
Stairway Width	36.00"	36.00"
Stairway Config	7/11	7/11
Designed Water Flow	800 GPM	800 GPM
Pump Motor	10 HP	10 HP

PRELIMINARY LAYOUT – FOR REVIEW AND APPROVAL ONLY.  
SPECIFICATIONS SUBJECT TO CHANGE  
NOT FOR CONSTRUCTION

CONFIDENTIAL – PROPERTY OF USA SLIDE, INC

**CUSTOM AQUAADRENALINE SLIDE**

**USA SLIDE**

USA SLIDE, INC  
1180 AIRPORT PARKWAY  
GAINESVILLE, GEORGIA  
30501 USA

PHONE: 770 297 1551  
1 800 872 7543  
FAX: 770 297 9633  
www.usaslide.com

MODEL CAAF-248L3	DRAWN BY RLP	DWG. DATE OCT 06, 2010
DWG SCALE 1/8" = 1'-0"	REVISION 5	DWG. NO. CAAF248L3